



HEAVY DUTY ENGINE DEGREASER

A solvent based formula that is a remarkably fast engine degreaser. It will remove grease, sludge, dirt, and tar from an engine within minutes. Simply spray on and hose off. Ideal for cleaning lawn mowers, marine engines, truck engines, motorcycle engines, and garage floors.

Removes Grease, Sludge, Dirt, & Tar

Directions:

Shake can well before using. Cover distributor using a plastic bag to avoid wetting. Spray generously on warm, dry engine. Let soak for 15 minutes. Hose off with strong stream of water.

After rinsing, immediately start engine and let engine run for 15 minutes to insure complete drying.

Handling:


Avoid contact with eyes and skin. In case of eye contact, immediately flush eye thoroughly with large amount of clean, clear water for 15 minutes. In case of skin contact, wash skin area with soap and water. Do not use near extreme heat sources, sparks, or open flame. Harmful if swallowed. If swallowed, DO NOT induce vomiting. Use only in ventilated area.

Order Information:

Part #	Container	Case Qty	Pallet Qty
4123I	14.5 fl. oz.	12	147
Container Height (in)	Case Dimensions L x D x H (in)	Case Weight (lbs.)	
9.56	11 x 8.25 x 9.75	14.76	

Typical Values:

Product Code	4123I
MSDS #	4123I
Specific Gravity	0.8250
Appearance	Colorless, Petroleum Distillate odor
Physical State	Aerosol
Boiling Point, °F	220 - 440° F
Vapor Density, BT	4.5 - 6.2
Vapor Pressure, BT	0.4 - 5.0 mmHG
Flash Point, °F	-156°F
Solubility	Not soluble in water
Propellant	Propane-Isobutane-n-Butane
Aerosol Flammability Level	Extremely Flammable
DOT Shipping Name	CONSUMER COMMODITY ORM-D CLEANING COMPOUND NOI NMFC 48580 SUB 3
VOC Compliant	CA: NO OTC: YES



4123I
Effective 05/09