

Installation Sheet

☐Application Vehicle

| 1991~2002 | Year | Mazda RX-7 | Vehicle Name |
|-----------|--------------|------------|--------------|
| 13B-REW | Engine Type | | |
| 103BKZ02 | Product Code | FD3S | Vehicle Code |

□Parts List

| | | | | _ | φ70 P110 | Gasket | 0 |
|-----|------|--------------------|-----|-----|------------------|-----------|---------|
| _ | | Instruction Manual | 3 | _ | Vehicle Specific | Muffler | \odot |
| Qty | Size | Part Name | No. | Qty | Size | Part Name | No. |

□Exhaust System Installation Procedure

XThe diagram only shows partial usage of the nuts and bolts. Please use all of them. Install the muffler according to the diagram below and hand tighten the nuts and bolts in place.

2. Take note of piping clearance, gasket positioning, tip position, chassis clearance and tighten

the nuts and bolts into position. Start from the catalytic converter side and work your way back

3.Be sure to confirm tail pipe positioning so that it does not touch the rear bumper. If the positioning is off, loosen the nuts and bolts and adjust accordingly. Failure to provide adequate clearance may cause unnecessary sound and may melt the bumper.

CAUTION

Be sure to check clearances between brake components, fuel line, and drive train components.

☐ Checkpoints after Installation

1.After installation, move the exhaust system side to side by hand to confirm clearances

2.Rev the engine to 2500rpm to check for any exhaust leaks.

3. Test drive the vehicle and check for exhaust leaks or unusual sounds.

4.If anything usual occurs in steps $1\sim3$, reinstall the muffler system.

5.Retighten all of the nuts and bolts after 100 \sim 200mi

